

Loader Model	Tire No.	Wheel (RIM)	Wheel / Tire Assy	Width	Rim Size	Maximum Ground Pressure (psi)	Ply Rating	Tire Inflation Pressure*		Wheel Stud	Lug Nut	Complete kits**
								(psi)	(kPa)			
85	42824SP	8732SP	42831SP/42830SP	5.9	15	53.14	4	30-36 psi	210-250 kPa	S/N Break	S/N Break	U-2749
85	42825SP	8733SP	42833SP/42832SP	8.5	15	39.86	4	45-50 psi	315-350 kPa	S/N Break	S/N Break	U-0644
105	46432SP	42888SP	46441SP/46440SP	8.5	15	44.24	6	45-50 psi	315-350 kPa	26188SP	5832SP	U-2588
105	42883SP	42889SP	42887SP/42886SP	10.5	15	35.63	6	40-45 psi	280-315 kPa	26188SP	5832SP	N/A
137	44025SP	25116SP	44016SP/44017SP	10	16.5	49.78	6	40-45 psi	280-315 kPa	26188SP	5832SP	U-2562
153	44025SP	25116SP	440167SP/44017SP	10	16.5	51.20	6	40-45 psi	280-315 kPa	26188SP	5832SP	U-2562
175	44024SP	36491SP	44020SP/44021SP	12	16.5	43.50	8	45-50 psi	315-350 kPa	26188SP	5832SP	U-2656
205	44024SP	36491SP	44020SP/44021SP	12	16.5	45.30	8	45-50 psi	315-350 kPa	26188SP	5832SP	U-2656
250	44024SP	29064SP	44022SP/44023SP	12	16.5	47.10	8	45-50 psi	315-350 kPa	26188SP	5832SP	U-2563
255	44024SP	29064SP	44022SP/44023SP	12	16.5	47.10	8	45-50 psi	315-350 kPa	26188SP	5832SP	U-2563
320***	44024SP	29064SP	44022SP/44023SP	12	16.5	47.10	8	45-50 psi	315-350 kPa	26188SP	5832SP	U-2563

*Follow owner / operator manual or information on tire regarding inflation

**Complete kits will have 4 tires with wheels (assembled - 2 LH & 2 RH)

***320 model is track unit. To convert to tires, U-3474 conversion kit required along with U-2563 tire kit (standard tires).

S/N Break (T85 Wheel Bolt and studs)

Up to LB002719 use Wheel Bolt part number 001904SP

LB002720 onward use 026188SP wheel stud and 5832SP